

Features

- 15.6 inch large screen for viewing convenience
- Three Working Modes: Monitoring, Surgery and Diagnosis.
- Simple and friendly operating display interface.
- Multi-display modes suitable for different applications: Standard Interface, Large font, ECG Standard Full Display, OXY, Trend Table, BP Trend.
- Built-in high capacity battery up to 3 hours of continuous
- VGA output for external display

Technique Specification

ECG

- Lead Mode: 5 Leads (I, II, III, AVR, AVL, AVF, V)
- Gain: 2.5mm/mV, 5.0mm/mV, 10mm/mV, 20mm/mV
- Heart Rate: 15-300 BPM (Adult); 15-350 BPM (Neonatal)

Resolution: 1 BPM Accuracy: ±1%

Sensitivity >200 uV(Peak to peak)

- ST measurement range: -2.0 ~ +2.0 mV
- Accuracy: -0.8mV~+0.8mV: ±0.02mV or ±10%, which is

greater

Other Range: unspecified

- Sweep speed: 12.5 mm/s, 25mm/s, 50mm/s
- Bandwidth:

Diagnostic: 0.05~130 Hz Monitor: 0.5~40 Hz Surgery: 1~20 Hz

Multi-parameter monitor

PM15B



SP₀2

- Measuring Range: 0 ~ 100 %
- Accuracy: 70% ~ 100% (±2 %)
- Resolution: 1 BPM

Optinal Parameters:

- Recorder (Printer)
- Resolution: 1%
- Pulse Rate: 20-250 BPM
- Accuracy: ±3 BPM
- Central monitoring system
- Dual IBP
- Etco2
- 12-lead ECG;
- Nellcor SpO2;
- Sun Tech NIBP.

NIBP

- Method: Oscillometry
- Measure mode: Manual, Auto, STAT
- Unit: mmHg, kPa
- Measure and alarm range:
- Adult Mode

SYS 40 ~ 280 mmHg DIA 10 ~ 225 mmHg MEAN 20 ~ 240 mmHg

Pediatric Mode

SYS 40 ~ 220 mmHg DIA 10 ~ 160 mmHg MEAN 20 ~ 170 mmHg

Neonatal Mode

SYS 40 ~ 135 mmHg 10 ~ 100 mmHg MEAN 20 ~ 110 mmHg

- Resolution: 1mmHg
- Accuracy: ±5mmHg

TEMP

- Measure and Alarm Range: 0 ~ 50 C
- Resolution: 0.1C
- Accuracy: ±0.1C

Standard Parameters:

ECG, RESP, TEMP, NIBP, SPO2, PR

RESP

- Method: Impedance between RA-LL or RALA
- Measurement Range: Adult: 10 ~ 120 BrPM Neonatal / Pediatric: 7 ~ 150 BrPM
- Resolution: 1 BrPM
- Accuracy: ±2 BrPM

Standard Configuration:

No.	Item	Qty
1	Main Unit	1
2	5-lead ECG cable	1
3	Disposable ECG Electrode	5
4	Adult Spo2 probe	1
5	Adult NIBP cuff	1
6	NIBP extension tube	1
7	Temperature probe	1
8	Power Cable	1
9	User Manual	1
10	Fuse	3

Packing:

- Single package size: 45*40*32 cm
- Single gross weight: 5.7 KG